

CONVEYOR TYPE DOUBLE TANK DISHWASHER

STANDARD



GT-CR2

POWER

Superior washing results. Sustained pressure powered by **ABB** motor. Stainless steel built bolt-on impeller housing.




SIMPLE

Simple operability with one-touch buttons and **UNIVERSAL** safety and energy-saving features such as auto door sensor and automatic conveyor operations.



DOUBLE

Double stainless steel tank, delivering **DOUBLE** capacity and handles overwhelming demand up to 268 racks an hour.



TECHNICAL DATA

Model:	GT-CR2
Dimensions (mm):	1652 (W) x 695 (D) x 1913 (H)
Loading height (mm):	450
Rack type (mm):	500 x 500
Machine net weight	402 kg

ELECTRICAL POWER LOADING

Voltage:	380V ~ 415V 50Hz 3 Phase
Electrical loading:	40 kW 56 A (<i>Alternative Heating</i>) 48 kW 81 A (<i>Full Heating</i>)
Wash tank heater:	2 x 9 kW
Booster tank heater:	4 x 9 kW
Wash pump:	2 x 1.5 kW ABB motor
Conveyor motor:	0.55 kW

OPERATING INFORMATION

Wash temperature:	55°C - 65°C
Rinse temperature:	82°C - 90°C
Wash rate (per hour):	268 racks, 6800 6" plates
Rinse usage:	<1 liter(s) per rack
Wash tank capacity:	2 x 83 liters
Booster tank capacity:	21 liters
Heating mode:	Available in Electric or Steam
Chemical dispensers:	Optional G-Star L dispenser (<i>sold separately</i>)
Automated Drain pump:	NA
Exhaust hood:	Optional fitting (<i>sold separately</i>)

