

# DOOR TYPE DISHWASHER

## ELECTRONIC CONTROL



GT-D1M (EC)

### POWER

**POWERFUL** washing standards. Sustained pressure to deliver extraordinary results. Selectable wash timing. Stainless steel impellers housing.



### DURABLE

Stainless steel chamber build. Built from industrial grade 304 stainless steel. **ENDURING** performance with zero-trouble experience.



### DIGITAL

**DIGITAL** displays and minimum cluttering provides a user-friendly experience. Simple usability and reliable components.



## TECHNICAL DATA

<b>Model:</b>	GT-D1M (EC-LE) / GT-D1M (EC)
<b>Dimensions (mm):</b>	697 (W) x 690 (D) x 1443 (H)
<b>Loading height (mm):</b>	420
<b>Rack type (mm):</b>	500 x 500
<b>Machine net weight</b>	122 kg

### ELECTRICAL POWER LOADING

<b>Voltage:</b>	220V ~ 240V   50Hz   1 Phase	380V ~ 415V   50Hz   3 Phase
<b>Electrical loading:</b>	3.5 kW   15 A ( <i>Alternative Heating</i> )	11 kW   15 A ( <i>Alternative Heating</i> ) 14 kW   20 A ( <i>Full Heating</i> )
<b>Wash tank heater:</b>	2 kW	3 kW
<b>Booster tank heater:</b>	2 kW	9 kW
<b>Wash pump:</b>	0.95 kW	
<b>Rinse pump:</b>	NA	

### OPERATING INFORMATION

<b>Wash temperature:</b>	55°C - 65°C
<b>Rinse temperature:</b>	82°C - 90°C
<b>Wash cycle (per rack):</b>	60/90 sec 70/90 sec *(EC-LE)
<b>Wash rate (per hour):</b>	60/40 racks 50/36 racks *(EC-LE)
<b>Rinse usage:</b>	<2 liters per cycle
<b>Wash tank capacity:</b>	36 liters
<b>Booster tank capacity:</b>	10 liters
<b>Chemical dispensers:</b>	NA
<b>Automated Drain pump:</b>	NA

