

UNDER COUNTER GLASS & DISHWASHER

STANDARD WITH BUILT-IN DISPENSER

FORM

The Standard variant **FORM** an excellent solution in glass and dishwashing for micro dining setting. Its compact and sturdy build gives it a convenient means to be placed anywhere in the kitchen or bar.



FIT

Compact build makes it easy to **FIT** into your kitchen. It has simple access to maintenance and servicing, saving chunks of time for the technical team.



FUNCTION

Full **FUNCTION** package with the built-in chemical dispensers and automated drain pump. Performs with a breeze and convenience through its complete and integrated system.



GT-U1M (C-BD)

TECHNICAL DATA

Model:	GT-U1M (C-BD)
Dimensions (mm):	600 (W) x 607 (D) x 751~771 (H)
Loading height (mm):	310
Rack type (mm):	500 x 500
Machine net weight	68 kg

ELECTRICAL POWER LOADING

Voltage:	220V ~ 240V 50Hz 1 Phase	380V ~ 415V 50Hz 3 Phase
	220V ~ 230V 60Hz 1 Phase [PH models]	220V ~ 230V 60Hz 3 Phase [PH models]
Electrical loading:	5.5 kW 24 A (Alternative Heating)	5.5 kW 8 A (Alternative Heating)
	-	8.5 kW 12 A (Full Heating)
	5.5 kW 41 A (Alternative Heating) [PH models]	5.5 kW 15 A (Alternative Heating) [PH models]
Wash tank heater:	3 kW	
Booster tank heater:	4.5 kW	
Wash pump:	0.62 kW	
Rinse pump:	NA	

OPERATING INFORMATION

Wash temperature:	55°C - 65°C
Rinse temperature:	82°C - 90°C
Wash cycle (per rack):	90 sec
Wash rate (per hour):	40 racks
Rinse usage:	<2.1 liters per cycle
Wash tank capacity:	23 liters
Booster tank capacity:	4.53 liters
Chemical dispensers:	Built-in system
Automated drain pump:	NA

